

00 1/190

OREGON PUBLIC LAND CORNER REPORT / RESTORATION REPORT
HOOD RIVER County Surveyor's Office

SECTION 36	TOWNSHIP 1 SOUTH	RANGE 9 EAST
----------------------	----------------------------	------------------------

COUNTY: **HOOD RIVER** DATE: **SEPT 23, 2009**

CORNER DESIGNATION: **Z-21**

Southwest Section Corner of Sec 36

(Please check one)	
<input type="checkbox"/>	Condition Report Only
<input type="checkbox"/>	Not Found
<input type="checkbox"/>	Renewed
<input type="checkbox"/>	Unrecorded
<input type="checkbox"/>	Surveyed In
<input type="checkbox"/>	Referenced Out

Previous Renewals / Surveys, etc. Original:
 GLO Surveyor Leonard Carter set a 3 ft iron post with brass cap in 1940, and established two bearing trees.
 A 23" white pine bears N15°E, 77 lks (50.82 ft) marked "T1SR9ES36BT".
 A 28" Doug Fir bears N47°W, 7 lks (4.62 ft) marked "T1SR9ES35BT".
 On 5/8/09 Beta Romio, USFS, found brass cap and pine stump.

Monument(s) & Accessories Found: (Condition & Source)
 On September 23, 2009, Tim Rouse, Fred Thomas, and Don Karsch found the 1940 GLO 2" brass cap, 1 ft above ground, in good condition. The NE white pine BT is now a 28" rotted stump, 2 ft high, with axe marks (no scribing visible) bears N16°E, 50.8 ft to the center. The NW fir BT is gone, found possible root hole at record bearing and distance.

Monument Detail: 1940 Brass Cap is Stamped:

T1S R9E
 |
S35 | S36
T1S R9E
S2
1940

(Note: this should be stamped "T2S")

Sketch:

Monument Set (Procedures and Description): No new monument set. We surveyed, cleared, blazed, and marked the south line of Section 36, with orange carsonite posts, for the U.S. Forest Service.

New Accessories: On September 23, 2009 we established 4 new bearing trees.
 A 10" Tamarack bears N71°E, 20.85 ft, scribed "T1S R9E S36 BT".
 A 10" Doug Fir bears S46°E, 27.45 ft, scribed "T2S R9E S2 BT".
 A 7" Spruce bears N60°W, 27.9 ft, scribed "T1S R9E S35 BT".
 A 11" Tamarack bears N8°W, 29.2 ft, scribed "T1S R9E S35 BT".

Location & Comments: Corner is 320 feet east of a skid road (K-Tag), in reprod unit of spruce, white pine, and Doug Fir. Distances to bearing trees are to a nail at side center. All bearing trees have a "54-3 BT" sign nailed on the front and a "54-9 Land Survey Monument" sign nailed to the back, with a brass washer nailed in lower face, and a 6" orange painted band.

Firm / Agency
ROUSE SURVEYING, INC.
 Address: 4900 NE 229th St, Ridgefield, WA 98642

Party Chief: **Timothy P. Rouse, Oregon PLS #2799**

Notes

Witness: **Fred Thomas, Oregon PLS #1018**
Don Karsch, Oregon PLS #1946

Compass Declination:
 Staff compass with Mag Dec of 16°E

SURVEYOR'S SEAL