SECTION OR SUBDIVISION NIACOR Sec 8	Corner No. 540
Twp. ZN, Range 8 Z, W.M.	CORNER DESCRIPTION
NO. REF. MARX & CHASE TO STARK ON STARKE W.O. REF. MARX & CHASE	
	CARD OF Z


Section or Subdivision 4 cor \$	Corner No. 540		
Twp. $\supset \bigcirc$, Range $S = _$, W.M.	CORNER DESCRIPTION		
FOUND: Bk.3-P.14 Stone 24XI2XI2 with a br set by U.S.A.E. by proportion in 193: Unrecorded now 16" D-Fir N7 1/2W 20" " S79E 6: Set Mon. 26" in ground in a stone & earth T2N R8E S5" 1/4 8 LS896	7.2' healed blaze O' healed blaze		
1987 W.O. Ref.			
CS # 87047	Card OF Z		

HOOD RIVER COUNTY

T	2N . R 8E, W.M. Corner Code No. CCOS40
Segi	regated Surveys:
Name	1/4 corner 5/8 Corner No.
	(DLC, HES, Tract, Mining Claim, Indian Allotment, Federal Reserve, Townsite)
1.	History of Corner Establishment and Subsequent Restoration:
	Found in 1973 by Hood River County Survey Department. Not remonumented
2.	Description of Evidence Found:
	Scribed rock and one bearing tree found in 1973 by Hood River County.
	술에 되어 가장이 하게 되었다고 하셨다는 그 이 등록이 됐다고 하는데 보고 그는 것이다.
3.	Describe Monument, Accessories and Corollary Data to Perpetuate this Corner Location Diagram corner and indicate meridian and reference to map of record. Surveyor's Field Book No: 3-75 Page No Date of work
9	1/4 Corner is a 12"x12"x24" rock with nail on top. 16" Dougals Fir with nail on south side 1 foot up bears East 5.40 feet 12" douglas Fir with nail with shiner on east side 1 foot up bears S 10°E 7.28 feet.
	그는 그는 그는 그는 그리고 있는 얼마 얼마나가 되었다. 그리고 있는 그리고 있는 것이 되었다. 그리고 있는 것이 없다.
Oreg	gon Plane Coordinates: North Zone, X 1,655,123.242 Y, 735,709.015
Seco	ond Order Accuracy. Derived from:
Pin	Pointed on Photo No. Date Located at
N	ote: X = Easting Y = Northing

12" x 12" x 24" Rock

DESCRIPT	ION OF SURVEY STATION		OREGON		
5		COUNTY HOOD RIVER			
NAME OF STA	ATION	JOB NO.	18-75		
CHIEF OF PARTY David Downing FIELD NOTES same DATE 11-18-75					
STATION MARK	SURVEY POINTS AND PROMINENT OBJECTS WHICH CAN BE SEEN FROM GROUND STATION	DISTANCE	BEARING		
E-1	l" iron pipe with yellow plastic cap marked HRC	240.91	N23°49'30"W		
	NOTE: All bearings and distances are Oregon State Plane Coordinates, North Zone				



EAST WI nail South side

15.40 WI nail South side

15t. up

12" Doug Fir - Set nail WI Shiner East side 1ft. up