

OREGON PUBLIC LAND CORNER REPORT / RESTORATION REPORT  
HOOD RIVER County Surveyor's Office

<b>SECTION</b> <b>36</b>	<b>TOWNSHIP</b> <b>1 SOUTH</b>	<b>RANGE</b> <b>9 EAST</b>
-----------------------------	-----------------------------------	-------------------------------

**COUNTY:** HOOD RIVER      **DATE:** SEPT 23, 2009

**CORNER DESIGNATION:** Z-23

**South 1/4 Section Corner of Sec 36**

(Please check one)	
<input type="checkbox"/>	Condition Report Only
<input type="checkbox"/>	Not Found
<input type="checkbox"/>	Renewed
<input type="checkbox"/>	Unrecorded
<input type="checkbox"/>	Surveyed In
<input type="checkbox"/>	Referenced Out

Previous Renewals / Surveys, etc. Original:  
 GLO Surveyor Leonard Carter set a 3 ft iron post with brass cap in 1940, and established two bearing trees.  
 A 30" Hemlock bears N80°E, 72 lks (48.18 ft) marked "1/4S36 BT".  
 A 25" Doug Fir bears N53°W, 90 lks (59.4 ft) marked "1/4S36 BT".  
 On 8/5/09, Berta Romio, USFS, found brass cap and two BT stumps.

Monument(s) & Accessories Found: (Condition & Source)  
 On September 23, 2009, Tim Rouse, Fred Thomas, and Don Karsch found the 1940 GLO 2" brass cap, 8" above ground, in good condition. The NE Hemlock BT is now a 36" rotted stump, 2 ft high, with axe marks (no scribing visible) bears N80°E, 47.0 ft to the center. The NW Doug Fir BT is now a 30" rotted stump, 1 1/2 ft tall, with partial face and scribing, "BT" visible, bears N53°W, 58.4 ft to the center.

Monument Detail: 1940 Brass Cap is Stamped:

**S 36**  
**1/4 -----**  
**1940**

Sketch:

Monument Set (Procedures and Description): No new monument set. We surveyed, cleared, blazed, and marked the south line of Section 36, with orange carsonite posts, for the U.S. Forest Service.

Nailed a 1 1/2" brass washer "PLS2799" in the bottom face of new bearing trees.

New Accessories: On September 23, 2009 we established 3 new bearing trees and 1 new bearing object.  
 A 10" Lodgepole Pine bears S76°W, 19.1 ft, scribed "1/4 S2 BT".  
 A 13" Nobel Fir bears N44°W, 29.1 ft, scribed "1/4 S36 BT".  
 A 11" Hemlock bears N21°E, 21.8 ft, scribed "1/4 S36 BT".  
 A basalt rock, 11'x5'x4' bears S84°E, 20.0 ft, with an "X BO" chiseled on front face.

Location & Comments: Corner is 30 feet north of USFS fire road #3511014 (K-Tag), in reprod unit of spruce, hemlock and Doug Fir, with thick underbrush. Distances to bearing trees are to a nail at side center. All bearing trees have a "54-3 BT" sign nailed on the front and a "54-9 Land Survey Monument" sign nailed to the back, with a brass washer nailed in lower face, and a 6" orange painted band.

Firm / Agency  
 ROUSE SURVEYING, INC.  
 Address: 4900 NE 229<sup>TH</sup> St, Ridgefield, WA 98642

Party Chief: Timothy P. Rouse, Oregon PLS #2799

Notes

Witness: Fred Thomas, Oregon PLS #1018  
 Don Karsch, Oregon PLS #1946

Compass Declination:  
 Staff compass with Mag Dec of 16°E

**SURVEYOR'S SEAL**