

RECEIVED
DATE 6/7/72

#1239

FILED

NEWTON SURVEYING CO.
HOOD RIVER, OREGON

JUN 12 1972

Carl Van Elsberg
COUNTY SURVEYOR

By _____
DEPUTY

FIELD NOTES

FOR: W.O. 1044-H-72 - Don Nunamaker - Survey of a 4 acre tract in the SW $\frac{1}{4}$ SW $\frac{1}{4}$ NE $\frac{1}{4}$ of Section 34, T. 3 N., R. 10 E., W.M., Hood River, County.

CREW: Brian Mostue, Instrumentman
Rich Cushman, Chainman

DATE COMPLETED: May 11, 1972

On May 8, 1972 I was requested by Mr. Don Nunamaker, Hood River, to survey and monument the corners of a tract of land lying along the East side of Frankton Hill Road opposite from Post Canyon Road. A search of the County Surveyor's records provided information concerning the sectional breakdown of the SW $\frac{1}{4}$ NE $\frac{1}{4}$ of Section 34 (Ref. County survey of proposed Westside Highway). A check was made of the information shown on the map of survey surrounding the SW $\frac{1}{4}$ NE $\frac{1}{4}$ of Section 34 which computed to be accurate and provided a basis for bearing control and dimensioning used throughout this survey.

The survey was begun by recovering existing monuments along Frankton Hill Road being the center of Section 34 (at Post Canyon Road intersection) and the center-north sixteenth section corner (at May Street intersection), which established the West boundary of the property. The Northwest property corner was established on this line at computed position and a second corner was set along this line as a corner common to an adjoining property also in the S $\frac{1}{2}$ SW $\frac{1}{4}$ SW $\frac{1}{4}$ NE $\frac{1}{4}$ of Section 34. The bearing of record was then extended easterly from the center of Section 34 toward the center-east sixteenth section corner, which established the South property boundary. The Southeast property corner was established on this line at computed position and a second corner was set along this line as a corner common to the previously mentioned adjoining property.

It was noted that the established corners fell within the rock walls surrounding a portion of the property and approximately 2 feet West of an old barbed wire fence along the East line of the previously mentioned adjoining property.

All property corners established during this survey were monumented with 5/8" iron rods with aluminum caps and set in concrete. Distances were measured with a 300 foot wire chain equipped with a tension handle and corrections were applied for temperature variations. Angles were measured with a Wild T-16 theodolite.

All corners found and established in the course of this survey, together with measured distances and angles are shown on the attached map, which by reference is made a part hereof.

I certify that this work was done under my direct supervision.

REGISTERED
PROFESSIONAL
LAND SURVEYOR

Norman A. Newton

OREGON
JULY 10, 1964
NORMAN A. NEWTON
654

SIGNED *Norman A. Newton*
Norman A. Newton

Registered Professional Land Surveyor
Oregon Certificate No. 654