Work Order No. 7313 March 19, 1990

# 90021

FIELD NOTES:

W.O. #7313 - Brad Fowler

CREW:

David L. Tuttle, Partychief Douglas J. Stroh, Assistant

DATE COMPLETED:

March 8, 1990

REFERENCE:

Wasco County Surveys No. 45 and 46 Hood River County Survey No. 7605 Hood River County Survey No. 80033

Hood River County Section Corner Monumentation Records

Tenneson Engineering Corporation was retained by Mr. Brad Fowler of Hood River, Oregon, on January 3, 1990, to provide a survey of the North one-half of the Southeast one-quarter of the Northeast one-quarter of Section 20, Township 2 North, Range 11 East, Willamette Meridian, Hood River County, Oregon, less and except a tract 20 rods North and South by 40 rods East and West in the Southwest corner thereof.

Search was made of existing survey office records in both Wasco and Hood River Counties and Tenneson Engineering Corporation files. The following information was recovered:

Northeast corner of Section 20 monumented with a 5/8 inch rebar with lead cap, Hood River County Survey No. 7605.

East one-quarter corner monumented with a 5/8 inch rebar with lead cap, Hood River County Survey No. 7605.

Southeast corner of Section 20, County brass cap monument.

South one-quarter corner of Section 20, a Hood River County brass cap monument.

North one-quarter corner of Section 20, an iron rod, RP tag, Hood River County Survey No. 80033 by Dan Cron.

In the field, a search was mounted for the West one-quarter corner of Section 20. Two healed over oak B.T.'s pursuant to Wasco County surveys No. 45 and 46, together with a marked stone were recovered and accepted for the position of this corner. The recovered B.T.'s appeared to be GLO trees at North 20° East at 6.6 feet and South 45° West at 11.2 feet. Ties were made to the four opposing quarter corners and the Northeast corner of Section 20 and a theoretical breakdown of the section calculated. From the East one-quarter corner a true line was run North along the East line of the Section with the

Field Notes - W.O. #7313 March 19, 1990 Page -2-

corners of the subject parcel set at the appropriate pro-rata distances. Also found in the course of this traverse were monuments set in Hood River County Survey No. 7605 at the one-sixteenth corner together with other monuments adjacent to the 64th corner unexplained. The survey was continued on around the subject parcel, establishing 5/8 inch iron rods with caps marked "LS #872". Basis of bearing was assumed to be North and South along the East line of the Section from the quarter corner North to the Northeast corner of the Section.

Monuments found and set in the course of survey are shown on the attached plat, Tenneson Engineering Corporation Work Order No. 7313 which, by reference, is made a portion of these notes.

Signed:

CHECKED AND APPROVED:

Tenneson Engineering Corporation

Donald J. Branton, President

wid h. Tul

REGISTERED PROFESSIONAL

LAND SURVEYOR

AVID L. TUTTLE