



CHARLES E. REYNOLDS

Surveyor and Consulting Forester

Phone: AT 7-4526  
5819 N. E. 25th Avenue  
Portland, Oregon 97211

June 20, 1966

FILED

JAN 13 1969

*Carl Van Elburg*  
COUNTY SURVEYOR

By

DEPUTY

Mr George Frey  
County Forester  
Court House  
Hood River, Oregon

Dear George:

Reference is made to survey in Section 23 T 2 N R 9 E. We started at the Southeast section corner and ran a compass line on var. of  $20^{\circ}$ . At south one quarter corner there is evidence of axe work on 30" pine stump to indicate it is original BT. We set stake at aprox. true corner location in relation to this BT. The calls all fit coming from the east into this corner. We continued west ~~chaining~~ the distance and the calls all fit. At about 14 ft. short of called distance from quarter corner we found the original stone which fits description. We set stake by the stone. We hit about 25 ft. north of the stone for latitude.

We then ran north on same variation and marked line at the road crossing. We hit at 5280 feet north the true corner which fell about 279 feet west and 22 feet south of the end of our mile of random line. We found one original BT to this corner and reset it as described on attached sheet. It falls about 620 feet east of the road at the east end of the dam at the Lower Green Point Reservoir.

Sincerely yours

*Charles E Reynolds*  
Charles E Reynolds

cc - Forest Ranger  
Parkdale District USFS

CORNER DESCRIPTION AS SET FOR CORNER TO SECTIONS: 14,15,22,23  
T 2 N R 9 E, Hood River County, Oregon

Found the original bearing tree called for a 15" diameter fir N 37° W 30 links. Could clearly see the T 2<sup>N</sup> R 9 E and S both on face and overgrowth. About 75 to 80 rings were counted on overgrowth to assure it is original. We could find no trace of the three other trees. We found an old stake which bears S 45° W 22.30 ft from the true corner location but it was not the original stake. On June 21, 1966 measuring from the N W bearing tree I set at the corner a 28" x 3/4" galv. iron pipe with a brass cap stamped ( 22, 23, 14, 15 ) with 8 " above ground in pile of rocks. It falls on top flat ridge about 620 feet east of the road at the east end of the Lower Green Point Reservoir. I blazed line out to road and set stake on the road. As a reference to the corner I drove four railroad spikes with a cross filed on the head of each into the base of the following trees. The distances are from the cross on the spike to the hole in center of corner pipe cap :

8 " diam White Fir	- Bears N 10° E	distance of 24.70 ft.
14" diam. White Fir	- Due East 53° W	distance of 20.21 ft.
12" diam White Fir	- Bears S 33° W	distance of 24.00 ft.
12" diam. doug. fir	- Bears N 82° W	distance of 21.10 ft.

No witness to setting corner but witness to finding bearing tree on June 17 was Stanley Thomson.

