



Basis of bearing is north as shown by deed and plat and is assumed to be correct.

FILED

JAN 9 1970
Carol Van Elburg
 COUNTY SURVEYOR
 BY _____ DEPUTY

○ = 3/4" IP SET
 ● = MON⁵ FD, AS NOTED

I, Roy L. Hill, hereby certify that this plat correctly represents a survey made under my direction in conformance with the requirements of the Oregon Land Surveyors Laws at the request of Mrs. Lena Paine. There are no visible encroachments other than those shown hereon.

REGISTERED
 OREGON
 LAND SURVEYOR

Roy L. Hill

JULY 9, 1962
 ROY L. HILL
 578

PLAT OF PAINE PROP.
 SE 1/4 NE 1/4 SEC. 12
 T2N RTE W.M.

J. S. DIELSCHNEIDER & ASSOC. INC.
 HOOD RIVER, OREGON

SURVEY: RLH DATE: 9/24/69
 DRWN: WCB DATE: 9/25/69
 SCALE: 1"=30' DRWG: 6961

JAMES S. DIELSCHNEIDER & ASSOCIATES, INC.

Engineering & Planning

Hood River (503) 386-2912

October 8, 1969

606 State Street

Hood River, Oregon 97031

Mr. Carlos Van Elsberg, Director
 Department of Public Works
 Hood River County
 P.O. Box 457
 Hood River, Oregon 97031

FILED

JAN 9 1970

Carlos Van Elsberg
 COUNTY SURVEYOR
 By _____
 DEPUTY

FIELD NOTES:

Mrs. Lena Paine, Project #6961, survey in the SE $\frac{1}{2}$ NE $\frac{1}{2}$ Sec. 12, T2N, R7E, WM
 Hood River County, Oregon.

CREW: R. L. Hill, Party Chief
 N. H. Weatherly, Chainman

DATES PERFORMED: Sept. 24, 1969

WEATHER: Fair, warm

On Sept. 12, 1969 our firm was retained by Mrs. Lena Paine to divide her property
 in Cascade Locks, into two parcels.

We referred to Hood River County Tax Map No. 2N 7 12 AD for information pertain-
 ing corners in the area.

CORNERS FOUND: Lot and block corners as shown on the attached plat.

CORNERS SET: 3/4" iron pipes were set at the points indicated on the attached
 plat. Lot corners were located by measurements along lines projected from the
 lot corners that were found. The northerly boundary of parcel #1 was set
 parallel to Ninth St. The westerly boundary was set parallel to Edgewood Drive,
 the 100 foot length of the northerly line was set as requested by Mrs. Paine.

Monuments found and set, together with the measured distances and bearings used
 on this survey, are shown on the attached map, which is by reference made a part
 of these notes.

I certify that this work was done under my direct supervision.

REGISTERED
 OREGON
 LAND SURVEYOR

Roy L Hill

JULY 9, 1962
 ROY L. HILL
 578