



A	20.32'
D	10 C.L.
T	126.69
F	5729.58
L	253.33

NARRATIVE:
 The Section Subdivision by D.L. Cron on his survey for Walt Kirkwood May 11, 1977 which was based in part on the survey by T.E.C. for Lewis Zeman in 1956 was held to be correct. The corner of sections 27-29-31-34 had been disturbed during construction. It was reset as noted from monuments found on the section line 27-34. The south line established at deed distances north on 5 1/2" cap and east of the section line on a line parallel to the south line of lot 12. The east line was made the deed distance in length and parallel to the section line. The eastern portion of the north line is deed distance from the NE corner at right angles to the section line. The western NE corner was set per Deed Book 37 Page 102 at right angles to the section line. The resulting distance to the corner to the south agrees with the deeds as well as can be expected given their ambiguity as to direction.

REGISTERED PROFESSIONAL LAND SURVEYOR
 Larry D. Bishop
OREGON
 JULY 11, 1980
 LARRY D. BISHOP
 896

Legend
 ● 5/8" x 30" Iron Rod Set
 ○ Monument Found
 Basis of Bearings - West Line Sec. 12 - Per D. Cron Survey - H.R. CO. # 77063

SURVEY FOR
ROBERT W. HUSKEY
 Portion Lot 12, Sec. 27, T.1N. R.10E
 Willamette Meridian, Oregon

BISHOP SURVEYING
 DATE Feb. 14, '80
 SCALE 1" = 30'
 PROJECT 80011

FILED
 APR 7 1980
 LARRY D. BISHOP
 OREGON SURVEYOR

SW. Cor. Set I.A.
 From D.L. Cron Survey
 Dated May, 1977
 Ed. B.C. 1 1/4" Conc. Top
 Is Broken off and pushed over.