





**CORNER INDEX NUMBERS**

J-9 Sec. Cor. 8-9-16-17  
 Found 18"x14"x10" stone at proper location from GLO BT, no visible marking. 46" fir N. 40° W 22.4 ft. Set brass disc on 2-1/2" pipe, BT's set  
 24" fir N 18° E 38.8 ft. marked "T2N R9E S9BT"  
 26" hemlock S 41° E 57.0 ft. mkd "T2N R9E S16BT"  
 BO set 1.5'x2'x2.5' exposed boulder S 55° W 9.0 ft. marked "X"

J-13 Sec. Cor. 9-10-15-16  
 Established by single proportion. Set alum. cap on 2-1/2" pipe, BT's set  
 16" D.fir N 04° E 23.0 ft. mkd "T2N R9E S10 BT"  
 10" D.fir S 80° E 15.5 ft. mkd "T2N R9E S15 BT"  
 12" D.fir S 39° W 14.0 ft. mkd "T2N R9E S16 BT"  
 6" D.fir N 13° W 18.3 ft. mkd "T2N R9E S9 BT"

J-15 1/4 Cor 10-15  
 Established by proportionment. Set alum. cap on 2-1/2" pipe, BT's set  
 14" hemlock S 15° W 14.3 ft. mkd "1/4 S15 BT"  
 11" fir N 11° W 11.8 ft. mkd "1/4 S10 BT"

J-17 Sec. Cor. 10-11-14-15  
 Found rotted stump. Stump w/scrubbing N 47° E 17.2 ft.; faced stump 15" dia. w/ax marks N 10° W 12.5 ft.; rotten stump w/scar S 87° E 14.5 ft. Set brass cap disc on 2-1/2" pipe & mound of stone, BO's set  
 3'x3.5'x1' exposed bldr. N 30° W 16.0 ft. mkd "X/BO"  
 2'x2.5'x1.5' exp. bldr. S 06° W 13.6 ft. mkd "X/BO"  
 5'x7'x8' exp. bldr. S 74° E 31.2 ft. mkd "X/BO"  
 BT set 4" fir N 52° E 19.5 ft. mkd "X"

L-13 1/4 Cor. 15-16  
 Established by proportionment. Set alum. cap on 2-1/2" pipe & mound of stone, BT's set  
 12" fir S 43° E 4.9 ft. mkd "1/4 S15 BT"  
 10" fir S 51° W 18.8 ft. mkd "1/4 S16 BT"

N-5 Sec. Cor. 17-18-19-20  
 Found 14"x10"x8" scribed stone set 10" in ground marked 3 notches east, 3 notches south. Found scribed down BT pine S 30° W 58 lks. to stump hole.

N-9 Sec. Cor. 16-17-20-21  
 Found original GLO BT's  
 24" fir N 30° E 37 lks. to face  
 24" fir S 70° E 52 lks. to face  
 23" fir S 41° W 38 lks. to face  
 Set brass disc on 2-1/2" pipe & mound of stone. BT's set  
 8" fir N 22° E 44.1 ft. mkd "T2N R9E S16 BT"  
 9" fir N 53° W 31.1 ft. mkd "T2N R9E S17 BT"

N-11 1/4 Cor. Sec. 16-21  
 Found BT's and stump hole depression.  
 20" fir stump N 70° E 5.9 ft. scribed  
 18" fir stump S 75° W 6.7 ft. faced  
 Set brass disc on 2-1/2" pipe & mound of stone. BT's set  
 6" fir N 54° W 37.5 ft. mkd "1/4 S16 BT"  
 6" fir S 82° W 16.4 ft. mkd "1/4 S21 BT"

N-13 Sec. Cor. 15-16-21-22  
 Established by proportionment. Set alum. cap on 2-1/2" pipe & mound of stone. BT's set  
 8" hemlock N 16° E 41.4 ft. mkd "T2N R9E S15 BT"  
 6" fir S 08° E 35.4 ft. mkd "T2N R9E S22 BT"  
 5" hemlock S 31° W 95.0 ft. mkd "T2N R9E S21 BT"  
 6" hemlock N 16° W 41.0 ft. mkd "T2N R9E S16 BT"

N-17 Sec. Cor. 14-15-22-23  
 Found 1" brass cap on 3/4" pipe in mound of stone. 2-1/2"x2-1/2" scribed wood post (broken). BT's found  
 10" white fir N 10° E 24.42 ft.  
 16" white fir S 90° E 20.13 ft.  
 14" white fir S 33° W 23.8 ft.  
 14" D.fir S 82° W 21.1 ft.  
 Snag w/visible scribing N. 38° W 20.5 ft.  
 Also found second stone mound S 58°18' W 19.8 ft. from brass cap (upon investigation second stone mound was found to be true corner position). Set 3/4" iron rod.

P-13 1/4 Cor. Sec. 21-22  
 Established by proportionment. Set alum. cap on 2-1/2" pipe & mound of stone. BT's set  
 9" fir S 64° E 12.7 ft. mkd "1/4 S22 BT"  
 6" fir S 84° W 5.8 ft. mkd "1/4 S21 BT"

R-1 N.W. Cor. Sec. 30  
 Found GLO scribed stone 14"x12"x5" set 10" in ground marked 4 notches north, 2 notches south. BT's found  
 20" fir N 52° E 12 lks.  
 36" fir S 30° E 9 lks. All open scribed faces  
 14" hemlock S 30° W 23 lks. as per original GLO  
 14" fir N 57° W 60 lks. scribes.

R-9 Sec. Cor. 20-21-28-29  
 Found notched stone in mound of stone. Remains of scribed BT in SE quadrant. 22" fir stump at GLO call in NE quadrant. Set brass disc on 2-1/2" pipe and mound of stone. BT's set  
 7" fir N 75° W 42.6 ft. mkd "T2N R9E S20 BT"  
 6" hemlock N 26° E 14.7 ft. mkd "T2N R9E S21 BT"  
 8" lodgepole pine S 70° E 13.5 ft. mkd "T2N R9E S28 BT"  
 11" hemlock S 22° W 8.2 ft. mkd "T2N R9E S29 BT"

R-11 1/4 Cor. Sec. 21-28  
 Established by proportionment. Set alum. cap on 2-1/2" pipe & mound of stone. BT's set  
 11" fir N 21° E 12.0 ft. mkd "1/4 S21 BT"  
 15" white fir S 69° E 17.7 ft. mkd "1/4 S28 BT"

R-13 Sec. Cor 21-22-27-28  
 Found rotten stump w/scrubbing S 54° W 11.2 ft.; rotted stump partial face no scribing S 43° E 25.1 ft.; rotted stump N 72° E 23.1 ft. Set brass cap on 2-1/2" pipe & mound of stone. BT's set  
 6" white fir N 15° W 4.1 ft. mkd "S21 BT"  
 8" fir S 15° W 13.1 ft. mkd "S28 BT"  
 14" fir S 50° E 26.0 ft. mkd "S27 BT"  
 6" fir N 38° E 18.5 ft. mkd "S22 BT"

T-9 1/4 Cor. Sec. 28-29  
 Found scribed stone and mound of stone with BT's  
 17" fir stump N 55° W 14.2 ft.  
 24" fir stump S 30° E 10.4 ft.  
 Set brass disc on 2-1/2" pipe & mound of stone. BT's set  
 15" fir S 46° E 8.3 ft. mkd "1/4 S28 BT"  
 9" fir N 46° W 4.8 ft. mkd "1/4 S29 BT"

V-1 S.W. Cor. Sec. 30  
 Found 24" pine stump w/scrubbing S 71° W 4.6 ft.; GLO stump remains N 59° E 9.2 ft. Set alum. cap on 2-1/2" pipe & mound of stone. BT's set  
 12" fir N 55° E 21.1 ft. mkd "T2N R9E S30 BT"  
 9" lodgepole pine S 68° E 24.3 ft. mkd "T2N R9E S31 BT"

V-9 Sec. Cor. 28-29-32-33  
 Established by double proportionment. Set brass disc on 2-1/2" pipe & mound of stone. BT's set  
 8" fir N 37° E 14.5 ft. mkd "T2N R9E S28 BT"  
 10" fir S 56° E 21.3 ft. mkd "T2N R9E S33 BT"  
 16" fir S 29° W 10.8 ft. mkd "T2N R9E S32 BT"  
 24" fir N 42-1/2° W 33.3 ft. mkd "T2N R9E S29 BT"

V-11 1/4 Sec. Cor. 28-33  
 Established by single proportionment. Set alum. cap on 2-1/2" pipe & mound of stone. BT's set  
 6" fir N 48° W 25.2 ft. mkd "1/4 S28 BT"  
 17" fir S 01° W 23.0 ft. mkd "1/4 S33 BT"

V-13 Sec. Cor. 27-28-33-34  
 Found rock with "X" on top 10" above ground & mound of stone, rotted 2"x2" post. BT's found  
 28" fir stump N 58° W 22.0 ft. partial face  
 30" fir stump S 28° W 9.0 ft. partial face  
 14" D.fir N 85° W 9.0 ft. healed face  
 18" D.fir S 04° W 16.0 ft. healed face  
 17" D.fir S 82° E 13.0 ft. healed "X"  
 Set brass cap on 2-1/2" pipe & mound of stone. BT's set  
 12" fir S 82° W 20.8 ft. mkd "S33 BT"  
 16" fir S 51° E 21.5 ft. mkd "S34 BT"  
 6" fir N 62° E 7.2 ft. mkd "S27 BT"  
 6" fir North 4.5 ft. mkd "S28 BT"

V-17 S.E. Cor. Sec. 27  
 Found stone and BT's  
 48" fir snag N 39°30' W 37.0 ft.  
 46" fir S 35°30' W 16.5 ft.  
 Stump S 86°30' E 6.6 ft.

X-9 1/4 Cor. Sec. 32-33  
 Found 12"x12"x8" stone, no visible marks, BT's  
 Down fir w/scrubbed face stump S 75° E 44.9 ft.  
 Set alum. cap on 2-1/2" pipe & mound of stone. BT's set  
 10" fir N 47° E 74.0 ft. mkd "1/4 S33 BT"  
 9" hemlock N 75° W 107.0 ft. mkd "1/4 S32 BT"

Z-9 Sec. Cor. 32-33  
 Found brass cap and scribed stone marked 4 notches east, 2 notches west. Found BT's  
 9" fir S 45° E 8.9 ft. mkd "X"  
 14" fir N 89° E 34.8 ft. mkd "X"  
 14" hemlock N 4-1/2° E 19.7 ft. faced

Z-13 Sec. Cor. 33-34  
 Found 5/8" iron rod with alum. cap. Found BT's  
 20" fir N 83° W 25.0 ft. mkd "S33 BT"  
 26" fir N 32° E 6.9 ft. mkd "S34 BT"  
 Brass cap N 72-1/2° E 17.10 ft.

**FILED**

AUG 19 1981  
 COUNTY SURVEYOR  
 DEPUTY

Date	No.	Revisions	By	App.
<b>KINGSLEY CORNER SEARCH                      AND REMONUMENTATION                      FOR MT. HOOD NATIONAL FOREST                      IN TWP 2N, RANGE 9E., W.M.                      Hood River County, Oregon</b>				
Design	TENNESON ENGINEERING CORP.			Scale NONE
Survey	Consulting Engineers 409 Lincoln Street The Dalles Oregon			Date 7-29-81
Drawn	Checked	Approved	Work Order No.	Sheet
S.D.H.			6002	2 of 2

81097 70