



1/4 CORNER
 Found - 1) B.L.M. 1940 stamped Brass Cap -
 2) 5" stamp of 30" D.F. - S.45°W. - 5.28'
 3) 1" stamp of 7" W.F. - N.59°E. - 23.10'
 4) 6" stamp of 11" W.F. - N.32°W. - 24.42'
 B.T.'s Set -
 1) 4" W.F. - N.65°E. - 336" - X" @ eye ht. & scribe BT @ base
 2) 4" D.F. - N.74°W. - 292" - X" @ eye ht. & scribe BT @ base

SECTION CORNER
 Found - 1) B.L.M. 1940 stamped Brass Cap -
 2) 14" D.F. 1940 BT (healed) N.13°E. - 12.54'
 3) 13" D.F. 1940 BT (healed) N.45°W. - 18.48'
 NOTE: @ 1/8" to West of here found
 D.L.C. 79 Brass Cap 0.2' South &
 0.5' West of calculated position

1/4 CORNER
 Found - 1) B.L.M. 1940 stamped Brass Cap -
 2) 1" stamp of 9" W.F. - N.06 1/2°W. - 33'
 3) Root Bowl of 11" W.F. - N.12°E. - 16.5'
 B.T.'s Set -
 1) 10" Hemlock - N.57°W. - 30.0' scribed "4535 BT"
 2) 9" Hemlock - N.31°E. - 96.8' scribed "4535 BT"

SECTION CORNER
 Found - 1) B.L.M. 1940 stamped Brass Cap -
 2) 4" stamp of orig. 55" D.F. BT - N.20°E. - 113.52'
 3) Remains of orig. 22" D.F. BT - S.55°W. - 28.38'
 4) 20" D.F. 1940 BT (healed) - N.06°E. - 125.4'
 5) 18" W.F. 1940 BT (healed) - N.81°W. - 83.82'

SECTION CORNER
 Found - 1) Stamp of 30" D.F. with axe marks - S.22°E. - 9.9'
 2) Uprooted 18" W.F. with scribing visible - N.23°E. - 40.26'
 3) Stamp of 22" D.F. - N.36°W. - 6.798'
 4) Bert 1 1/2" I.F. - N.70°W. - 1.25'
 5) 1/2" I.F. - N.80°06'20"W. - 10.75'
 Set - 1) Set 3" Aluminum Cap stamped
 2) 5" D.F. - N.28°E. - 35.8' - scribed "TIN RSE 533 SC BT"
 3) 6" Noble - N.35°W. - 26.4' - scribed "TIN RSE 533 SC BT"

CLOSING CORNER U.S.
 Found - 1) B.L.M. 1940 stamped Brass Cap
 2.35' South of Base Line -
 2) 22" D.F. 1940 BT (healed) S.10°E. - 105.6'
 4) 17" D.F. 1940 BT (healed) S.48°W. - 9.1024'

CLOSING CORNER
 Found - 1) B.L.M. 1940 stamped Brass Cap
 0.65' South of Base Line -
 2) 14" D.F. 1940 BT (healed) S.22°E. - 38.94'
 3) 19" D.F. 1940 BT (healed) S.25°W. - 51.48'

SCALE 1" = 600'
 600' 0 600'
 182.88m 0 182.88m
 Basis of Bearing as per
 Oregon North Zone Coordinate
 System as per H.R.C. 10/25/76
 survey control

POSTING & MONUMENTATION

- 1) POSTING** - Lines shown as "USDA Forest Service Property Line Posted" are marked by 6' long orange fiberglass posts marked with U.S.F.S. sign 54-2. Said posts are set at a maximum interval of 150' & so as to be intervisible if the ground were cleared. All trees 6" or greater in diameter within 3' of line were blazed - U.S.F.S. trees double blazed & private trees single blazed.
- 2) BEARING TREES** - Bearing trees set are blazed with a 5'x18" scribed blaze placed as close to the ground as possible with a brass disc stamped "51028" nailed at the bottom of said 5'x18" scribed blaze unless noted. All bearing trees set or found have the following:
 - A 4 1/2" x 5" B.T. tag attached to face at eye height.
 - A 7" x 10" U.S.F.S. tag warning against destroying attached to back at eye height.
 - A 6" red band painted around tree above signs.
- 3) CORNER MONUMENTS** - Corner monuments set are 2" x 30" aluminum pipes with a stamped 3" aluminum cap affixed. Said 2" x 30" aluminum pipes are placed at the bottom & are set 2 1/2" in the ground unless noted. At all corner monuments set or found a 7" x 10" U.S.F.S. tag warning against destroying attached to an orange fiberglass post was set, in addition orange fiberglass posts were set within 3' to 5' of corner on U.S.D.A. Forest Service property lines.

NARRATIVE

The Base Line thru R.9 E. of the W.M. was originally surveyed by David P. Thompson in 1868 & 1869. Said Base Line was then resurveyed in 1884 by Newton Clark.
 In 1940 the B.L.M. did a dependent resurvey of the Base Line thru R.9 E. and a partial survey of T.15, R.9 E.
 On August 11, 1982 the U.S.D.A. Forest Service contracted the survey of several of their holdings located within the Hood River Ranger District. This particular survey is of Area #2 of said contracted survey. All field angles were turned with a Wild T-1. All distances were measured with a H.P. 3805A. Minimum position closure required was 1:5000. Field notes are contained in D.L.C. Field Books 826 & 83-3.

CERTIFICATION

I Danny L. Cron, a registered land surveyor in the State of Oregon hereby certify that this plat & the notes hereon, or attached, are a correct representation of a survey I performed from February to mid June of 1983 for the U.S.D.A. Forest Service in accordance with the statutes of the State of Oregon and with the articles of my contract: Said contract being PINE FLAT CADASTRAL, contract # 52-0-0467-2-00546.
 Danny L. Cron
 Danny L. Cron - Registered Land Surveyor - ORE Lic # 1028

U.S.D.A. FOREST SERVICE
 PROPERTY LINE POSTED

"SURVEY"
 FOR - U.S.D.A. Forest Service
 LOCATION - The South Line
 of Sections 34 & 35 of
 T.1N., R.9E., W.M.
 HOOD RIVER COUNTY,
 OREGON

REGISTERED
 PROFESSIONAL
 LAND SURVEYOR
 Danny L. Cron
 OREGON
 AUGUST 22, 1975
 DANNY L. CRON
 1028
 June 11, 1983

D.L.C. Surveying
 Dan Cron
 5634 Trout Creek Road
 Parkdale, Oregon
 97041
FILED
 DEC 22 1983
 Richard J. Amodeo
 COUNTY SURVEYOR