

POSTING & MONUMENTATION-

POSTING - Lines shown as U.S.D.A. Forest Service Line Posted are marked by 6' long orange fiberglass posts marked with U.S.F.S. sign 54-2. Said posts are set at a maximum interval of 150' & so as to be intervisible if the ground were cleared; EXCEPTING in the lava beds in which spacing averaged 300'. All trees 6" or greater in diameter within 3' of line were blazed. U.S.F.S. trees double blazed & private trees single blazed.

BEARING TREES - Bearing trees set are blazed with a 5"x18" scribed blaze placed as close to the ground as possible with a brass disc stamped 251028 affixed at the bottom of said blaze. All bearing trees set or found have the following: a) A 4 1/2"x15" B.T. tag attached to face @ eye height. b) A 7"x10" U.S.F.S. tag warning against destroying attached to back @ eye ht. c) A 6" red band painted around tree.

CORNER MONUMENTS - Corner monuments set are 2"x30" aluminum pipes with a 3" stamped aluminum cap affixed. Said 2"x30" aluminum pipes are flared at the bottom & are set 24" in the ground unless noted. At all corner monuments set or found a 7"x10" U.S.F.S. tag warning against destroying attached to a orange fiberglass post was set; in addition orange fiberglass posts were set within 3' to 5' of corner on U.S.D.A. Forest Service lines posted.

1 S.W. Cor. Sec. 36-3C.

Found BLM 1940 stamped brass cap as per D.L.C. 6/11/83 Survey

2 Cor. #1 of HES 139

Found marked stone as per G.L.O. Set 2"x30" al. pipe with 3" al. cap. Cap stamped: [Stamp: API HES 139 1984 PLS 1028] B.T.'s Found: stamp of 15" W.F. - S. 18.5' - 56.8' - healed blaze stamp of 16" W.F. - S. 32' W. - 48.8' - " B.T.'s Set: 7" Hemlock - N. 85.5° E. - 24.3' - scribed API HES 139 BT 8" W.F. - N. 62° W. - 30.0' - scribed API HES 139 BT

3 N.W. Cor. Sec. 2-CC

Corner & B.T.'s destroyed by road construction - did not reset.

4 S. 1/4 Cor. Sec. 36-3C.

Set 2"x30" al. pipe with 3" al. cap. From 1940 B.T. - Cap Stamped: [Stamp: TMR 95 1/4-36 52 AP 1984 PLS 1028] B.T.'s Found: 17" D.F. - N. 30° W. - 38.28' with healed blaze (1940) B.T.'s Set: 11" D.F. - N. 41° W. - 45.1' - scribed 1/4 536 SC BT 9" D.F. - N. 69° E. - 25.1' - " 1/4 536 SC BT

5 Cor. #6 of HES 139

Found marked stone as per G.L.O. which had been disturbed by catwork - Set 2"x30" al. pipe with 3" al. cap. Cap stamped: [Stamp: AP 6 HES 139 1984 PLS 1028] B.T.'s Found: 15" D.F. - S. 44° E. - 17.8' - healed blaze (1940) 17" D.F. - S. 11° W. - 21.1' - " (1940)

6 N. 1/4 Cor. Sec. 2-CC

Set BLM 1940 stamped brass cap which had been uprooted by catwork. B.T.'s Found: 19" D.F. - S. 20.5° - 38.3' - healed blaze (1940) 20" D.F. - S. 24° W. - 44.9' - " (1940)

7 S.E. Cor. Sec. 36-3C.

Found BLM stamped brass cap. B.T.'s Found: 10" D.F. stamp - N. 13° E. - 48.8' - scribe part visible 18" Maple - N. 29° W. - 7.9' - healed blaze (1940) B.T.'s Set: 7" W.F. - N. 60° E. - 22.2' - scribed TMR 1055315C BT

8 N.W. Cor. Sec. 1-CC

Found BLM 1940 stamped brass cap. Found 1910 C.C. 6.6' South. True Closing Corner Found T.E.C. stamped brass cap 4.8' North

9 W. 1/6 Sec. 1-CC

Set 2"x30" al. pipe with 3" al. cap. Cap stamped: [Stamp: S3 TMR 95 W 1/6 CC S1 TMR 95 1985 PLS 1028] B.T.'s Set: 9" D.F. - S. 85° E. - 80.0' - scribed W 1/6 S1 BT 14" D.F. - S. 30° W. - 92.2' - " W 1/6 S1 BT

10 N. 1/4 Cor. Sec. 1-CC

Found Railroad spike as set by single proportion as per T.E.C. 11/4/75 survey

11 S.E. Cor. Sec. 31-3C.

Found BLM 1940 stamped brass cap buried 6" as per T.E.C. 11/4/75 survey.

12 E. 1/4 Cor. Sec. 1

Found 12" diam. old cedar fence post with wire to the N., S., & W. Corner was accepted due to said physical evidence with supporting survey support. Said position being in agreement with CS. #48 & C/456 & current E/45.6.

Set 2"x30" al. pipe with 3" al. cap. Cap stamped: [Stamp: FIS 1/4 R9E R10E 51 1/4 1985 PLS 1028] B.T.'s Set: 7" W.F. - N. 17° E. - 11.1' - scribed 1/4 56 BT 6" W.F. - N. 55° W. - 12.5' - " 1/4 51 BT Found T.E.C. single prop. being 34.45' @ 11.8° E.

13 C. 1/4 Cor. Sec. 1

Set 2"x30" al. pipe with 3" al. cap. Cap stamped: [Stamp: FIS R9E C 1/4 1985 PLS 1028] B.T.'s Set: 10" D.F. - N. 64° E. - 46.2' - scribed C 1/4 51 BT 8" D.F. - S. 16° E. - 54.3' - " C 1/4 51 BT Found T.E.C. C/4 being 13.65' & 11.7' W.

14 C.W. 1/6 Sec. 1

Set 2"x30" al. pipe with 3" al. cap. Cap stamped: [Stamp: FIS R9E W 1/6 C 1 1985 PLS 1028] B.T.'s Set: 10" D.F. - N. 52° W. - 40.8' - scribed W 1/6 51 BT 18" W.F. - S. 42° E. - 104.2' - " W 1/6 51 BT

15 W. 1/4 Cor. Sec. 1

Found BLM 1940 brass cap as set from orig. 1910 evidence.

16 S. 1/4 Cor. Sec. 1

Found marked stone as per G.L.O. 1910 Survey. Set 2"x30" al. pipe with 3" al. cap. Cap stamped: [Stamp: FIS R9E S 1/4 1985 PLS 1028] B.T.'s Found: 20" Pine - N. 85° W. - 29.7' - scribed S 1/4 51 BT 36" Fir - down remains - S. 47° E. - 74.6' B.T.'s Set: 11" D.F. - S. 02° E. - 54.8' - scribed S 1/4 51 BT

17 S.E. Cor. Sec. 1

Found 1/2" axle buried 12" ±. Corner was accepted on basis of the following supporting evidence: a) 10" old cedar post 147' south b) @ 258' ± W. of Disbrow Creek vs. G.L.O. 251' call c) Found possible N.E. B.T. on edge of swampy ground. d) Corner was re-monumented in 1910 by G.L.O. & current position fits pre 1920 surveys.

Set 2"x30" al. pipe with 3" al. cap. Cap stamped: [Stamp: FIS R9E S 1/4 1985 PLS 1028] B.T.'s Set: 15" Alder - S. 56° E. - 56.0' - scribed S 1/4 51 BT Power Pole - N. 80° E. - 132.8' - # D11A9 N.E. cor 818 bldg. - S. 70° E. - 26.3' Power Pole - N. 80° W. - 131.6' - has transformer

18 E. 1/4 Cor. Sec. 12

Found position as per Perkins 1950 iron pipes to the North setting in old N/S fence line. Vicinity of 1/4 cor. was cleared in the early 1960's. Corner was re-monumented in 1910 by G.L.O. & current position is in agreement with pre 1920 surveys. (continued)

18-continued

Set 2"x30" al. pipe with 3" al. cap. Cap stamped: [Stamp: FIS 1/4 R9E R10E 51 1/4 1985 PLS 1028] B.T.'s Set: 7" Pear - N. 22° W. - 21.2' - B.T. tag only 10" Pear - N. 18° E. - 20.7' - B.T. tag only

19 W. 1/4 Cor. Sec. 12

Found BLM 1940 stamped brass cap as set from orig. 1910 evidence. B.T.'s Found: 22" D.F. - N. 36° W. - 19.1' - healed blaze 33" D.F. - N. 47° E. - 19.1' - " "

20 N.W. Cor. Sec. 12 CDD

Set 2"x30" al. pipe with 3" al. cap. Cap stamped: [Stamp: NW COR OF TMR 95 1/4 1985 PLS 1028] B.T.'s Set: 21" D.F. - S. 84° E. - 22.6' - scribed 1/4 51 2 BT 22" D.F. - N. 33° W. - 14.5' - " 1/4 51 2 BT

21 N.E. Cor. Sec. 12 CDD

Set 2"x30" al. pipe with 3" al. cap. Cap stamped: [Stamp: NE COR OF TMR 95 1/4 1985 PLS 1028] B.T.'s Set: 20" D.F. - N. 80° W. - 7.7' - scribed 1/4 51 2 BT 6" W.F. - S. 16° W. - 11.6' - " 1/4 51 2 BT

22 S. 1/4 Cor. Sec. 12

Found corner as per H.R.C. 4/25/77 survey.

23 S.W. Cor. Sec. 12 CDD

Set 2"x30" al. pipe with 3" al. cap. Cap stamped: [Stamp: SW COR OF TMR 95 1/4 1985 PLS 1028] B.T.'s Set: 11" D.F. - S. 73° E. - 2.8' - scribed 1/4 51 3 BT 8" D.F. - N. 33° W. - 12.5' - " 1/4 51 3 BT

24 W. 1/6 Cor. Sec. 12 & 13

Found 58" IR as per H.R.C. 4/25/77 survey. Set 2"x30" al. pipe with 3" al. cap. Cap stamped: [Stamp: FIS R9E W 1/6 51 3 1985 PLS 1028] B.T.'s Set: 23" D.F. - N. 05° E. - 26.0' - W 1/6 51 3 BT 31" D.F. - S. 66° E. - 70.0' - W 1/6 51 3 BT

25 S.W. Cor. Sec. 12

Found BLM 1940 stamped brass cap as set from orig. 1910 evidence. B.T.'s Found: 10" D.F. - N. 25° E. - 110.2' - healed blaze 28" D.F. - S. 57° W. - 63.4' - " " 18" D.F. - N. 47° W. - 21.8' - " " 40" D.F. - S. 81° E. - 178.9' - " "



Danny L. Cron



July 10, 1985

FILED

JUL 12 1985

RICHARD ARNOLD COUNTY SURVEYOR

Danny L. Cron

85032 1042