



SCALE 1"=300'

BASIS OF BEARING AS PER HOOD RIVER COUNTY SURVEY  
DATED MARCH 25, 1985, DRAWING NO. 85015

REGISTERED  
PROFESSIONAL  
LAND SURVEYOR  
*Richard J. Arnold*  
OREGON  
JULY 15, 1983  
RICHARD J. ARNOLD  
2038

FILED  
MARCH 23, 1992  
*Richard J. Arnold*  
COUNTY SURVEYOR  
92022

**NARRATIVE**

THIS SURVEY WAS PERFORMED AT THE REQUEST OF THE HOOD RIVER COUNTY FORESTRY DEPT. IN ORDER TO MARK THE EAST, WEST, AND SOUTH BOUNDARIES OF THE NW1/4NW1/4 OF SECTION 8 T2NR11E. THE NORTH 1/16 BETWEEN 7&8 AND THE WEST 1/16 BETWEEN 5&8 HAD BEEN PREVIOUSLY SET IN 1985 BY THE HOOD RIVER COUNTY SURVEYOR. ALL SECTION AND QUARTER CORNERS NEEDED TO COMPLETE THE BREAKDOWN OF SECTION 8 WERE FOUND AND TIED BY FIELD TRAVERSE WITH THE EXCEPTION OF THE SOUTH QUARTER CORNER. J.B. GOIT, WASCO COUNTY SURVEYOR, SET A STONE IN 1899 FROM ORIGINAL EVIDENCE. WE FOUND THIS STONE NEAR A FENCE INTERSECTION. JOHN LELAND HENDERSON FOUND THIS STONE AND FENCE INTERSECTION IN 1907. WHEN WE FOUND THIS STONE IT HAD BEEN MOVED ABOUT 15 FEET SOUTH TO SUPPORT ANOTHER FENCEPOST. I SET A 2 INCH PIPE AND BRASS CAP AT THE INTERSECTION AND PLACED GOITS STONE ALONGSIDE. WE THEN CALCULATED AND SET THE NW1/16 CORNER AND BLAZED THE EAST, SOUTH, AND WEST BOUNDARIES OF THE NW1/4NW1/4.

HOOD RIVER COUNTY SURVEY DEPARTMENT  
SURVEY OF THE N.W.1/4 OF SECTION 8, T.2N.,R.11E.,W.M.  
HOOD RIVER COUNTY, OREGON