



- LEGEND
- Found corner of record
  - Found point of acceptance
  - Set 5/8"x30" IR with plastic cap
  - Calculated point from records
  - ( ) Record distance

REFERENCES:

1. Page 105,106 of Plats, 1900
2. Survey #77049, 1977
3. Survey #78001, 1978

Deed reference: Bk. 74, P. 691 of Deed Records  
 Basis of Bearings: CL of May Street between County monuments E-3 & E-4 taken as true.

SURVEY & TRAVERSE NARRATIVE: A closed field traverse was made around Blocks 1 & 2 using a 10" total station and related equipment. Raw closure in excess of 1:10000 was balanced by compass adjustment. The block and lot corners of Block 2 that were not recovered were calculated and/or set by proportion to the original plat distances after subtraction for public streets. Work conducted during June 24-29, 1992.

- NOTES:
1. North angle point of concrete wall falls 0.29' north of calculated point; held as best position for block corner.
  2. PK nail from Ref. 2 falls 0.5' north of calculated point. It and interior corners of Ref. 2 not accepted.

Trantow Surveying, Inc. makes no warranty as to matters of unwritten title, adverse possession, estoppel, acquiescence, etc.

T. N. TRANTOW SURVEYING, P. L. S.  
 P. O. Box 287, Bingen, Washington 98605  
 (509) 493-3111

SURVEY FOR  
**HENRY SPENCER**  
 HOOD RIVER CO., OR.

REGISTERED  
 PROFESSIONAL  
 LAND SURVEYOR  
*Terry N. Trantow*  
 OREGON  
 JUL 15, 1977  
 TERRY N. TRANTOW  
 179

**FILED**  
 JUL 17, 1992  
*Richard G. Arnold*  
 COUNTY CLERK

Surveyed by DC Date 6-25-92 Scale 1" = 100'  
 Drawn by TT Date 6-27-92 Sheet 1 of 1  
 Checked by TT Date 6-29-92 Project No. 92829

29 JUNE 1992