



SET 5/8"X30" IRON ROD WITH I-1/2" OR 2-1/2 " AL, CAP
SET I-1/2"X30" IRON PIPE OR A 7/8"X30" IRON ROD WITH 2-1/2 BRASS OR AL, CAP

FOUND MONUMENT OF RECORD \* \* FENCE LINES FROM TIES NEAR CORNERS.

W.T. WITNESS TREES (SCRIBED) WITH NAIL APPROXIMATING THE CENTER.

B.T. ORIGINAL GLO BEARING TREE

( ) ( GLO DISTANCE OR ANOTHER SURVEYOR'S DISTANCE OR DEED CALL)

REFERENCES:
G.L.O. NOTES, SURVEYS VOL. AND PAGE, OR FILM NR.
DIELSCHNEIDER SURVEY 84020
BISHOP SURVEY 79063, 88057-I AND 87047 GAYLORD SURVEY 86069 AND 8306 COUNTY SURVEY 1204 AND 18-75 1975 PERKINS SURVEY OF CEMETERY IN 1958

EQUIPMENT: 6" TOTAL STATION, CLOSED LOOP, CAL. MAY. 1993, CLOSURE BY LEAST SQUARES, 1/55345, 0.052' MAIN LOOP 1/39092, 0.022' SUB LOOP.

D2AB SURVEYING INC 22 COTTONTAIL RIDGE ROAD WHITE SALMON, WA. 98672 PHONE NO. 509-493 3376

CITY OF CASCADE LOCKS

REGISTERED PROFESSIONAL LAND SURVEYOR

Dannis Peoples

OREGON JANUARY I 1988 DENNIS & PEOPLES 2325

SECTION 12 T2N R7E WM HOOD RIVER CO.