NARRATIVE: THE PURPOSE OF THIS SURVEY WAS TO DEFINE THE PROPERTY BOUNDARY OF FOUND THE SECTION CORNER OF RECORD IN THE MONUMENT CASE TAX LOT 1100. THE NORTH LINE OF FOLTS SHOWS A PLAT DISTANCE OF 1012.9 FEET FROM THE NORTHEAST CORNER OF FOLTS TO THE NORTHWEST CORNER OF THE SUBDIVISION AND A TIE DISTANCE OF 70.5 FEET TO THE NORTHWEST CORNER OF THE SOUTHWEST QUARTER OF THE NORTHWEST QUARTER OF THE SECTION FOR A TOTAL DISTANCE OF 1083.4 FEET. WE MEASURED A TOTAL DISTANCE OF 1093.44 FEET. THE DIFFERENCE IN DISTANCE BEING A HIATUS OF 10.04 FEET. THE SUBDIVISION WAS ONLY PLATTED TO THE WEST RIGHT OF WAY OF THE COUNTY ROAD AND IN ALL PROBABILITY THE 70.5 FEET WAS A SCRIVENER'S ERROR AND SHOULD HAVE BEEN 80.5 FEET. I THEREFORE WENT ALONG WITH THE OTHER SURVEYS OF RECORD AND MEASURED FROM THE NORTHEAST CORNER OF FOLTS AS SHOWN ON THE FACE OF THE PLAT. SEE FACE OF PLAT FOR FURTHER DETAILS. LOCATION OF SURVEY: LOT 13 AND THE NORTH 30 FEET OF LOT 12 OF FOLTS SUBDIVISION OF ODELL, LOCATED IN SECTION 26, SCALE: 1"=30 FEET TOWNSHIP 2 NORTH, RANGE 10 EAST, WILLAMETTE MERIDIAN, COUNTY OF HOOD RIVER, STATE OF OREGON. REGISTERED **PROFESSIONAL** LAND SURVEYOR OREGON JULY 13, 1979 ROY O. GAYLORD 1815 LINE TABLE BEARING NO. DISTANCE Expires: June, 2005 L1 S 16.15'35" E 10.87 5/8" IRON ROD FOUND, LS 1815. 1 1/2" IRON PIPE FOUND THIS CORNER WAS SET TO 5/8" IRON ROD WITH A LS 1028, 5/8" PERPETUATE THE NORTHEAST "EWE & I ADDITION-PHASE 1" FOUND, LS 1028 IRON ROD SET IN THE CORNER OF FOLTS SUBDIVISION AS EXISTING 6' TALL MIDDLE. POINT OF S 89°03'23" E 473.49 MONUMENTED BY NORM NEWTON PRIVACY FENCE BEGINNING FOR "EWE & I IN 1972 AND AS FOUND BY PLS N 89°00'37"\ ADDITION-PHASE 1". 1971 IN JUNE, 1992. 81.39 30.00 S 89°01'25" E S 89°03'23" E 237.36 20.0 S 89'03'23" E 236.13 NORTHWEST CORNER /2" IRON 538.57 THEXISTING THE N 89°02'01" W 774.70 (774.7') HELD THE PLAT DISTANCE FROM THE NORTHEAST OF THE SOUTHWEST ROD FOUND 9 GARAGE | 90 QUARTER OF THE CORNER OF FOLTS SUBDIVISION. NORTHWEST QUARTER 20.0' THE NORTH - SOUTH LOT LINE IS SHOWN ON THE THE ORIGINAL PLAT LOT DISTANCE WAS OF SECTION 26. FOLTS SUBDIVISION PLAT AS BEING NORMAL TO THE 238.2' TO THE RIGHT OF WAY OF THE NORTH LINE OF THE SUBDIVISION. PLEASE REFER TO OLD EXISTING COUNTY ROAD AND THEN THE C.S. #7203 FOR CONFORMATION OF THE 70.5 FEET ON WEST TO THE 1/16 DIRECTION. EXISTING 5' TALL CORNER. WE MEASURED 81.39 FEET AN UNRECORDED PIPE WAS FOUND AT OR NEAR THE CHAIN LINK FENCE BASIS OF BEARING: WEST TO THE 1/16 CORNER FORM THE OLD NORTH RIGHT OF WAY LINE OF MUD ALLEY EXISTING HIGHWAY EASTERLY RIGHT OF DRIVE DID NOT AGREE WITH OUR RIGHT ANGLE N.A.D. 1983, OREGON NORTH, GRID BEARINGS SOLUTION. WE DID NOT USE THE PIPE BUT DO TAX LOT 1100 SHOW A LOCATION TIE FOR REFERENCE PURPOSÉS. Δ= 2°34'34" C1 R=331.56 30.00 REFERENCES: L = 14.91HOOD RIVER COUNTY WARRANTY DEED #20031973. HOOD RIVER COUNTY SURVEY #97016. S 89'02'01" E HOOD RIVER COUNTY SURVEY #7203. 30.00 210.02 PLAT OF FOLTS SUBDIVISION OF ODELL. L3 S 15'50'57" E 14.91 HOOD RIVER COUNTY PARTITION PLAT #9210. HOOD RIVER COUNTY PARTITION PLAT #9622. OSHD DRAWING #6B-26-20, DATED 1948. HOOD RIVER COUNTY DRAWING #5F-0808, DATED MARCH THIS RIGHT OF WAY IS BASED ON THE REALIGNED OREGON STATE HIGHWAY #282. THE MAP 5F-0808 AND IS DATED MARCH, 1942. LEGEND: SET 5/8" X 30" IRON ROD WITH PLASTIC CAP FOUND MONUMENT OF RECORD AS NOTED. CALCULATED, NOT FOUND OR SET DEED OR PLAT CALL 1 1/4" IRON PIPE FOUND & NOT OF TERRA SURVEYING RECORD FILED L2 S 89'02'01" E 9.29 DATE: JULY, 2003 SCALE: 1" = 30' PROJECT: 203046 TAX ASSESSORS MAP: 2N-10-26BC P.O. BOX 617

PROPERTY BOUNDARY SURVEY

for

ALLEN & ALETHIA LARSEN

FOUND THE QUARTER CORNER OF RECORD IN THE

MONUMENT CASE.

Paces; 9-16-04 1515

CS 2004 061

HOOD RIVER, OREGON 97031

E-Mail: terra@gorge.net

PHONE & FAX: (541) 386-4531