


FILED

JAN 31 2007
Randy D. Terra
 COUNTY SURVEYOR
 WASH. COUNTY

- LEGEND:**
- SET 5/8" X 30" IRON ROD WITH PLASTIC CAP
 - FOUND MONUMENT OF RECORD
 - CALCULATED, NOT FOUND OR SET
 - ⊙ TERRA CONTROL POINT
 - () DEED OR PLAT CALL
 - ☀ CONIFEROUS TREE
 - ☁ DECIDUOUS TREE
 - ⊖ POWER POLE
 - ⌵ GUY ANCHOR



REFERENCES:
 HOOD RIVER COUNTY SURVEY NO. 84054
 HOOD RIVER COUNTY SURVEY NO. 80052
 HOOD RIVER COUNTY SURVEY NO. 2000 080
 HOOD RIVER COUNTY SURVEY NO. 1301
 OREGON STATE HIGHWAY RIGHT OF WAY OF A PORTION OF HIGHWAY 35, MAP 8B-9-21, DATED MAY, 1958.

LOCATION OF SURVEY:
 A PORTION OF THE SOUTHWEST QUARTER OF THE SOUTHWEST QUARTER OF SECTION 34, TOWNSHIP 1 NORTH, RANGE 10 EAST WILLAMETTE MERIDIAN, HOOD RIVER COUNTY IN THE STATE OF OREGON.

BASIS OF BEARING:
 N.A.D 83, OREGON NORTH, GRID BEARINGS

VERTICAL DATUM:
 N.A.V.D 88

NARRATIVE:

THE PURPOSE OF THIS SURVEY WAS TO PROVIDE A PROPERTY BOUNDARY SURVEY AS WELL AS A TOPOGRAPHIC DETAIL ON SUBJECT PROPERTY. TOPOGRAPHIC DETAIL ON PAGES 1 AND 2 OF THIS SURVEY ARE SHOWN USING A 1 FOOT CONTOUR INTERVAL. **"PAGES 1 AND 2 NOT FILED"**

THERE IS NO GUARANTEE TO THE CORRECTNESS OR COMPLETENESS OF THE UNDERGROUND UTILITIES LOCATIONS.

BASED ON MONUMENTATION FOUND IN THE FIELD WE WERE ABLE TO DEFINE THE SOUTHWEST QUARTER OF THE SOUTHWEST QUARTER OF SECTION 34. THE DEED CALL "TO A POINT 30 FEET FROM THE CENTER LINE OF A CREEK" WAS FIELD VERIFIED AND MEASURED ALONG THE SOUTH PROPERTY LINE TO TERMINATE ON THE NORTH-SOUTH 1/16 LINE OF THE SOUTHWEST QUARTER OF SECTION 34. THE DEED DISTANCE WOULD HAVE FELL BEYOND THE EAST LINE OF THE SOUTHWEST QUARTER OF THE SOUTHWEST QUARTER. THIS POSITION FELL WITHIN REASONABLE TOLERANCES OF THE CREEK. THE CORNERS SHOWN ON SURVEY WERE MONUMENTED WITH 5/8" TERRA IRON RODS.

THE STATE HIGHWAY NO. 35 IS OF VARIABLE WIDTH IN THIS AREA. THE SURROUNDING SURVEYS SHOW THE STATE HIGHWAY TO BE A 150 FOOT RIGHT OF WAY. THIS DISTANCE AGREES WITH AN OLD FENCE LINE FOUND ON THE PROPERTY. THE STATE HIGHWAY RIGHT OF WAY MAP WAS USED TO CALCULATE THE SET IRON RODS AT THE NORTHWEST AND SOUTHWEST CORNERS OF THE SURVEYED PROPERTIES.

C3
 $\Delta = 4'09''34''$
 $R = 1145.92$
 $L = 83.19$
 $CH = 83.17$
 $CB = N 09'09''00'' W$

THE CALCULATED CORNER IS DEFINED AS STATION 12974.69 AND 645' FROM THE FOUND SECTION CORNER BETWEEN 33 & 34.

C1
 $\Delta = 9'28''00''$
 $R = 1145.92$
 $L = 189.34$
 $CH = 189.12$
 $CB = N 11'42''54'' W$

C2
 $\Delta = 9'28''00''$
 $R = 1070.92$
 $L = 176.94$
 $CH = 176.74$
 $CB = N 11'42''54'' W$

BOUNDARY AND TOPOGRAPHIC SURVEY
 for
EAST FORK IRRIGATION

REGISTERED PROFESSIONAL LAND SURVEYOR
Roy O. Gaylord
 OREGON
 JULY 13, 1979
 ROY O. GAYLORD
 1815
 Expires June, 2007

DATE: OCTOBER, 2006
 SCALE: 1" = 80'
 PROJECT: 206037BOUNDARY
 ASSESSORS MAP: 1N 10E 34

P.O. BOX 617
 HOOD RIVER, OREGON 97031

PHONE & FAX: (541) 386-4531
 terra@gorge.net

FOUND 5/8" IRON ROD WITH PLASTIC HRC CAP.

S 89°14'52" E
 1339.31